

[54] PUP JOINT WITH INTEGRAL WING NUT RETENTION SHOULDER

[75] Inventor: Paul A. Crawford, Stephenville, Tex.

[73] Assignee: FMC Corporation, Chicago, Ill.

[21] Appl. No.: 962,182

[22] Filed: Oct. 31, 1997

Related U.S. Application Data

[63] Continuation of Ser. No. 651,646, May 22, 1996, abandoned.

[51] Int. Cl.⁶ F16L 19/025

[52] U.S. Cl. 285/23; 285/354; 285/387;
285/388

[58] Field of Search 285/23. 354. 386.
285/387. 388. 321

[56] References Cited

U.S. PATENT DOCUMENTS

1,186,021	6/1916	Mezger 285/388
2,298,109	10/1942	Frank 285/388
3,751,077	8/1973	Hiszpanski 285/386
4,116,477	9/1978	Wahoski 285/386

4,124,234	11/1978	Clark 285/388
4,575,044	3/1986	Gentry 285/388
4,648,634	3/1987	Kelch 285/387
4,877,270	10/1989	Phillips 285/387
5,160,174	11/1992	Thompson 285/387
5,362,109	11/1994	Pacnt 285/388

FOREIGN PATENT DOCUMENTS

723284	3/1980	U.S.S.R. 285/387
17810	1/1914	United Kingdom 285/387

Primary Examiner—Eric K. Nicholson
Attorney, Agent, or Firm—Henry C. Query, Jr.

[57] ABSTRACT

A pup joint is provided which comprises a length of pipe, a female sub integral with one end of the pipe and having external threads formed thereon, a male sub integral with the other end of the pipe, a wing nut for threadedly connecting the male sub to the female sub, a set of retainer segments for retaining the wing nut on the pup joint, and a retention shoulder formed on the male sub to maintain the wing nut and retainer segments on the male sub. In a preferred embodiment of the invention, the pipe and the male and female subs are comprised of a single forging, and the retention shoulder is formed by machining the male sub.

3 Claims, 2 Drawing Sheets

